

Del-Ron[®] BioSynthetic 0w30



The oil: based on **biodegradable(80%)** and **renewable(60%, based on bioderived carbon atoms)** lubricating oil, so-called "BioSynthetic" lubricants, **OECD-301F 28day: 52%**
Newest achievement made by excellent lubrication- and additive technology !
Synthetic oils like performance and service life !

Very good for small engines, both bensin&diesel, when 0w30 viscosity oil is needed.

Excellent properties:

- your engine will stay clean longer and it will maintain it's maximun performance better.
- diminish you engine wear and withstands biofuels
- very good low temperature properties, lubricates quickly at start-up
- **versatile, might be used as manual gearbox oil 70w80 GL-4 !**

For long oil change intervals. The oil will maintain it's superior qualities even when used for a long period. This is extremely important when having long oil change intervals.

Manufactured using a high stability viscosity improver.

This way the oil has achieved **superior qualities**; **high stability** and **stability under stress**, **good endurance against high temperatures** and **good properties of diminishing the wearing of engine parts**.

Suitable for normal everyday street use and also for catalytic converters(CAT) and particle filters(DPF), low sulphated ash(SAPS) and phosphorous content.

So-called: LowFriction, ability to lower fuel consumption and reduce wear of engine parts.

Do not mix with other oils or additives !

SAE:	0w30	ACEA-16: A5/B5, C2
Visc. +40c, cSt	52,9	ACEA-12: A1/B1, A5/B5, C2
Visc. +100c, cSt	9,9	ACEA-08: A1/B1, A5/B5, C2/C3
Visc.index:	176	API: (SL) SM / SN / CF
Visc.CCS(-35C,0w)	6.060 mPas	PSA: B71-2290
Pour Point:	< -51 C	Renault: RN-0700
HTHS (+150c)	3,3 mPas	VW: 503 / 506
SAPS:	0,8 %	
Phosphorous:	0,08 %	
TBN	8,0	
Colour:	Natural/Brownish	

**Save Nature
and...
Press
the
Pedal....**

Values may vary/change, Please note that the properties do not constitute a specification and are not an warranty or guarantee of any properties.

